



## **[Citrix 1Y0-731](#)**

**Exam Name:** Citrix Netsoaler 8.0: Administration Exam

**Q & A :** 98 Q&As

**[Pdf Demo](#)**

### **Quality and Value for the 1Y0-731 Exam**

[Exam4Dumps Practice test](#) for Citrix Citrix Other Certification 1Y0-731 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development. our products of the latest 1Y0-731 exam dumps, 1Y0-731 questions and answers is the real 1Y0-731 practice test.

[Citrix Other Certification Certification](#) 1Y0-731 Q&A are created by senior IT lecturers in exam4dumps certification Q&A network and Citrix Other Certification product experts combination PROMETRIC or VUE true-to-date environmental examination of the original title.

The Questions & Answers cover the latest real **1Y0-731 practice test** and with all the correct answer. we promise the 1Y0-731 Q&A for Citrix Other Certification 1Y0-731 (Citrix Netsoaler 8.0: Administration Exam) examination of original title complete coverage. 1Y0-731 Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

exam4dumps professional provide Citrix Other Certification 1Y0-731 the newest Q&A, completely covers 1Y0-731 test original topic. With our complete Citrix Other Certification braindumps resources, you will minimize your Citrix Other Certification cost and be ready to pass your 1Y0-731 tests on Your First Try, 100% Money Back Guarantee included!

### **100% Guarantee to Pass Your 1Y0-731 Exam**

If you do not pass the Citrix Other Certification 1Y0-731 exam on your first attempt using our Exam4Dumps **1Y0-731 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

### **Downloadable, Interactive 1Y0-731 Testing engines and PDF Version**

Our Braindumps Preparation Material provides you everything you will need to take a [Citrix Other Certification certification](#) examination. Details are researched and produced by [Citrix Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

**Free 1Y0-731 Exams:**

***This is demo only, this pdf do not include the questions and answers pictures***

1. Scenario: An administrator is planning to deploy NetScaler systems in an environment with multiple IP subnets, one of which is non-routable. The company is an online retailer and needs outbound connections from the non-routable subnet in order to verify credit cards. What will an administrator need to configure to meet the company's requirements?

- A. SIP
- B. USIP
- C. RNAT
- D. USNIP
- E. Layer 2 mode

Answer: C

2. A large e-commerce company is planning on integrating NetScaler systems into their network environment. The company requires that the original client IP addresses be recorded in the web server logs.

Which two features on the NetScaler could accomplish this? (Choose two.)

- A. USIP
- B. RNAT
- C. USNIP
- D. Edge mode
- E. Client IP insertion

Answer: AE

3. Scenario: An administrator introduced two new servers into a server farm that can handle more traffic than the older servers. The current load balancing method set for the virtual server managing the traffic for this group of servers is Least Connections. The administrator wants to maintain the load balancing method but also wants to use the new servers to improve performance by having them take more of the traffic than the older servers.

Which advanced option must the administrator configure to achieve this?

- A. Spillover
- B. Max Client
- C. Backup vserver
- D. Service Weights
- E. Global Setting Override

Answer: D

4. A company is planning on implementing NetScaler systems in High Availability pairs.

Which entry in the NS.CONF file of the secondary system needs to be unique from those of the primary system?

- A. VMAC
- B. Node ID
- C. MIP address
- D. NSIP address

Answer: D

5. Scenario: A company is deploying a NetScaler system in a network environment with some subnets open to the public Internet and one non-routable subnet. The administrator plans on enabling Use-Subnet-IP mode and disabling Use-Source-IP mode.

Which two IP addresses can the administrator set as source IP addresses for connections to back-end servers? (Choose two.)

- A. VIP
- B. MIP
- C. SNIP
- D. NSIP

Answer: BC

6. What does an administrator need to configure in order for a NetScaler system to advertise virtual IP addresses, directly connected routes and static routes on the upstream routers?

- A. Static Routes
- B. Link Load Balancing
- C. Route Health Injection
- D. Front-end Health Check

Answer: C

7. An administrator plans to configure a NetScaler system to resolve DNS queries using an external DNS server with an IP address of

10.10.10.1.

Which command could the administrator use to configure this?

- A. add nameserver DNS1 10.10.10.1
- B. add lb vserver DNS1 dns 10.10.10.1
- C. add server DNS1 10.10.10.1 -external
- D. add nameserver DNS1 dns 10.10.10.1 -local

Answer: A

8. Scenario: An administrator is planning on deploying a NetScaler system into a network environment using SNMP. The administrator plans on enabling the 11 SNMP traps relating to request and response rates.

Which two objects must the administrator configure in order for the SNMP traps to send alerts? (Choose two.)

- A. SNMP destination
- B. Source IP address
- C. Threshold levels for the traps
- D. Additional IP addresses on which the SNMP service can respond to SNMP queries

Answer: AC

9. Which type of VLAN is used when an administrator leaves the NetScaler system interfaces on the default VLAN?

- A. Tagged
- B. Port-based
- C. MAC-based
- D. Protocol-based

Answer: B

10. Which two modes could a NetScaler system be deployed in if all traffic must pass through the NetScaler? (Choose two.)

- A. HA inline
- B. HA one-arm
- C. Stand-alone inline
- D. Stand-alone one-arm

Answer: AC

11. What must an administrator configure the NetScaler log to record in order to know when someone has altered the system configurations?

- A. Access logs
- B. Event messages
- C. System counters
- D. Audited commands

Answer: D

12. Which option must an administrator enable on a NetScaler system to route packets that are not destined for the NetScaler?

- A. L2 mode
- B. L3 mode
- C. Static route advertisement
- D. Dynamic route advertisement

Answer: B

13. Scenario: A company based in Beijing was unable to reach their data center for more than a week due to a nearby earthquake. The company now has Distributed Data Centers in multiple regions, including a disaster recovery center, to increase redundancy. The company wants their new NetScaler systems to load balance these centers.

Which NetScaler feature will allow load balancing across these centers only for redundancy?

- A. Global Server Load Balancing to make load balancing decisions between the two sites
- B. TCP-based content switching to make a decision between the load balance virtual servers
- C. Proximity-based Global Server Load Balancing based on the RTT of client requests to virtual servers
- D. SNMP load monitor bound to each location and bound to the default NetScaler metric table and with the appropriate SNMP OIDs to load balance the different locations

Answer: A

14. The auditing and security policy of a company requires that all transactions that can be logged must be logged.

Which option must an administrator configure a syslog server for to meet this requirement?

- A. Device counters
- B. System counters

- C. HTTP transactions
- D. Audited commands

Answer: D

15. Scenario: An administrator is configuring monitoring for web servers in the environment that often results in services being marked as DOWN because of slow back-end servers. The administrator wants to configure the virtual server and services so that existing connections stay open when a service is marked down but not when a virtual server is marked DOWN.

How must the administrator configure the service and virtual server to reflect this dependency?

- A. set lb vserver lbv1 -downStateFlush DISABLED  
set service svc1 -downStateFlush ENABLED
- B. set lb vserver lbv1 -downStateFlush ENABLED  
set service svc1 -downStateFlush ENABLED
- C. set lb vserver lbv1 -downStateFlush DISABLED  
set service svc1 -downStateFlush DISABLED
- D. set lb vserver lbv1 -downStateFlush ENABLED  
set service svc 1 -downStateFlush DISABLED

Answer: D

16. How many untagged VLANs can an administrator configure on a single interface?

- A. 1
- B. 2
- C. 16
- D. 256
- E. 4,096

Answer: A

17. Scenario: A company has distributed Internet sites and installations are spread across multiple network locations and requires load balancing to be based on the client's proximity to the site, with the least amount of configuration.

What must the administrator do to ensure GSLB uses the appropriate load balancing method?

- A. Enable and configure Dynamic Proximity based Global Server Load Balancing.
- B. Enable Dynamic Network Proximity based on the RTT of the client accessing the load balancing virtual server.
- C. Enable DNS view based Static Proximity through an Advanced expression to extract the client IP and compare it to the subnet of the site.
- D. Enable Proximity based Global Server Load Balancing and use the location's database to enter the MAC address of all the clients and the corresponding site to which they should make the connection.

Answer: A

18. A multinational company with two server farms wants to set-up a NetScaler system with High Availability as shown in the attached exhibit without using content switching.

How many virtual IP addresses will the administrator need for the environment set up to work?

Click the Exhibit button to view the environment.

- A. One
- B. Two
- C. Three
- D. Four

Answer: B

19. An administrator should configure Link Aggregation on a NetScaler system when \_\_\_\_\_. (Choose the correct option to complete the sentence.)

- A. redundancy on a half duplex operation is required
- B. redundancy on an operation across multiple data rates is required
- C. network connections between LAN switches and network servers require more than 1Gb/sec
- D. network connections between LAN switches and network servers require more than 8 Gb/sec

Answer: C

20. An SNMP manager attempted to poll for an OID but received the error message: "response timeout."

Which two options could the administrator have misconfigured for SNMPv2 to cause this error message? (Choose two.)

- A. SNMP user
- B. SNMP group
- C. SNMP manager
- D. SNMP community

Answer: CD

More [1Y0-731 dumps](#) Information

**Related 1Y0-731 dumps**

1Y0-A05	1Y0-A09	1Y0-A13	1Y0-264	1Y0-A08
1Y0-308	1Y0-A11	1Y0-A03	1Y0-A02	1Y0-256
1Y0-A06	1Y0-731	1Y0-A04	1Y0-740	1Y0-309
1Y0-900	1Y0-800	1Y0-A01	1Y0-326	1Y0-306

**Other Citrix dumps**

1Y0-222	1Y0-613	1Y0-A09	1Y0-614	1Y0-308
1Y0-A06	1Y0-327	1Y0-A13	1Y0-611	1Y0-256
1Y0-252	1Y0-962	1Y0-913	1Y0-A14	1Y0-800
1Y0-258	1Y0-326	1Y0-A08	1Y0-740	1Y0-A02